

Specification Sheet

Description **Fuelchief DC100**

Part No **DC100**



The DC100 is a compact and unique tank that only takes up a car parking space, which is impressive. Occupying such a small footprint makes the DC100 a popular choice and a great solution for those operations that have limited room available, yet still need fast and reliable access to fuel. Below are some of the key features of this product.

- 🔒 10,450L model with large secure cabinet to house all pumps and equipment
- 🔒 Full height access door with 3-way locking system and anti-levering design for extra security
- 🔒 Cabinet has access hatch through roof to allow safe servicing of tank vent
- 🔒 Hempel C4-High Marine grade paint system
- 🔒 Lockable access door to fuel management terminal, switching and dry-break coupling
- 🔒 Spill sump in cabinet base to contain spillage
- 🔒 Improved inner tank design with no internal bracing
- 🔒 Sloped floor in inner tank for better water catchment and recovery
- 🔒 Water inspection and suction port housed under lockable hatch
- 🔒 Large access manhole for maintenance and inspection of inner tank
- 🔒 Extra feed and return ports for running auxiliary equipment
- 🔒 Offset fill pipe with Todo Dry-Break coupling for rapid refuelling
- 🔒 Lockable fill point with integrated dipstick
- 🔒 1100 LPM rated & approved overfill prevention valve for safe filling and prevention of accidents
- 🔒 Base of tank sealed in an anti-rust underseal

Ext Dimensions (w,d,h)	Capacity (total)	Capacity (safe fill)	Weight (empty)
2310 x 2996 x 2550mm	10,450L	9,900L	2470kg
Design Approval	Tank Design Standard	Tank Design Standard	
TNK 15025	AS1692	AS1657	

*Due to custom nature of tank, weight may vary depending on application and design, does not include ladder in overall length or width

